



# Ceiling & Floor

## DC Inverter



Sleep Mode



Auto Restart



Auto Defrosting



Fresh Air



Anti-Cold Air Function



Timer



Independent Dehumidification

# Ceiling & Floor DC Inverter

## Specifications: Ceiling & Floor DC Inverter

Model		MUE-36HRDN1-Q	MUE-36HRDN1-R	MUE-60HRDN1-R
Power supply	V-ph-Hz	220~240-1-50	380-415-3-50	380-415-3-50
Cooling performance				
Capacity	Btu/h	36000	36000	55000
Input	W	3250	3125	5040
Current	A	14.9	6.2	8.7
EER	W/W	3.25	3.15	3.2
Heating performance				
Capacity	Btu/h	38000	38000	58000
Input	W	2950	2900	4680
Current	A	13.5	5.6	8.1
COP	W/W	3.58	3.3	3.63
Indoor unit				
Indoor air flow(Hi/Med/Lo)	m3/h	1800/1600/1350	1800/1600/1350	2300/1900/1700
Indoor noise level(Hi/Med/Lo)	dB(A)	54/49/45	54/49/45	54/49/46
Dimension (WxDxH)	mm	1285x675x235	1285x675x235	1650x675x235
Packing (WxDxH)	mm	1360x755x313	1360x755x313	1725x755x313
Net/Gross weight	kg	30/35	30/35	38/44
Outdoor unit				
Dimension(WxDxH)	mm	990x345x965	990x345x965	938x392x1369
Packing(WxDxH)	mm	1120x435x1100	1120x435x1100	1095x495x1505
Net/Gross weight	Kg	75/84.5	81/91	107/120
Refrigerant Type/Quantity				
Type		R410A	R410A	R410A
Charged volume	Kg	2.65	2.6	4.6
Refrigerant Piping				
Liquid side/Gas side	mm(inch)	Φ9.52/Φ15.9(3/8"/5/8")	Φ9.52/Φ15.9(3/8"/5/8")	Φ9.52/Φ15.9(3/8"/5/8")
Max. pipe length	m	65	65	65
Max. difference in level	m	30	30	30

### Remarks:

1. The above design and specifications are subject to change without prior notice for product improvement.
2. The sound levels in the table above reflect the levels as taken in an anechoic chamber.

### Dealer Details: