



Ceiling & Floor



Sleep Mode



Auto Restart



Auto Defrosting



Fresh Air



Anti-Cold Air Function



Timer



Independent Dehumidification

Ceiling & Floor (R410A)

Specifications: Ceiling & Floor (R410A)

Model		MUE-36HRN1-Q	MUE-36HRN1-R	MUE-48HRN1-R	MUE-60HRN1-R
Power supply	V-ph-Hz	220~240-1-50	380~415-3-50	380~415-3-50	380~415-3-50
Cooling performance					
Capacity	Btu/h	36000	36000	48000	55000
Input	W	4170	3980	5060	6400
Current	A	19.4	7.0	8.4	10.5
EER	W/W	2.53	2.65	2.78	2.52
Heating performance					
Capacity	Btu/h	40000	39500	52000	60000
Input	W	3894	3700	5063	5800
Current	A	18	6.5	8.6	9.6
COP	W/W	3.01	3.13	3.01	3.03
Indoor unit					
Indoor air flow(Hi/Med/Lo)	m3/h	1750/1400/1250	1750/1400/1250	1750/1400/1250	2300/1800/1600
Indoor noise level (Hi/Med/Lo)	dB(A)	53/48/44	53/48/44	53/48/44	55/49/46
Dimension (WxDxH)	mm	1285x675x235	1285x675x235	1285x675x235	1650x675x235
Packing (WxDxH)	mm	1360x755x313	1360x755x313	1360x755x313	1725x755x313
Net/Gross weight	kg	29/36	29/36	31/36	39/45
Outdoor unit					
Dimension(WxDxH)	mm	990x345x965	990x345x965	900x350x1170	900x350x1170
Packing(WxDxH)	mm	1120x435x1100	1120x435x1100	1032x443x1307	1032x443x1307
Net/Gross weight	Kg	87/97.2	85/95	93.2/105	97/108
Noise levels	dB(A)	61	61	63	63
Refrigerant Type/Quantity					
Type		R410A	R410A	R410A	R410A
Charged volume	Kg	2.6	2.4	3.25	3.2
Refrigerant piping					
Liquid side/Gas side	mm(inch)	Φ9.52/ Φ19(3/8"/3/4")	Φ9.52/ Φ19(3/8"/3/4")	Φ9.52/ Φ19(3/8"/3/4")	Φ9.52/ Φ19(3/8"/3/4")
Max. pipe length	m	30	30	50	50
Max. difference in level	m	20	20	25	25

Remarks:

1. The above design and specifications are subject to change without prior notice for product improvement.
2. The sound levels in the table above reflect the levels as taken in an anechoic chamber.

Dealer Details: